

	CX720	CX740	CX760	CX780	CX820	CX840	CX860	CX880
Return system								
Roto-thresher™	1	1	1	1	2	2	2	2
Returns indicator on InfoView™ monitor	●	●	●	●	●	●	●	●
Grain elevator								
High capacity grain elevator	●	●	●	●	●	●	●	●
Graintank								
Capacity (litres)	7,600	7,600	9,000	9,000	9,000	9,000	10,500	10,500
Central filling, folding bubble-up extension	●	●	●	●	●	●	●	●
Remote control graintank covers	●	●	●	●	●	●	●	●
Unloading speed (litres/sec.)	105	105	105	105	105	105	105	105
Engine								
Type	NH675TA/AG	NH675TA/AH	NH675TA/AJ	NH675TA/AB	NH675TA/AJ	NH675TA/AB	IVECO F2B	IVECO F3A
Gross engine power ISO TR 14396, at rated speed [kW/hp(CV)]	170/231	185/252	207/281	220/299	207/281	220/299	245/333	275/374
Governor type	electronic	electronic	electronic	electronic	electronic	electronic	electronic	electronic
Power boost [kW/hp(CV)]	–	–	–	–	–	–	20/27	20/27
Fuel tank								
Capacity (litres)	500	500	500	750	750	750	750	750
Transmission								
Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Gearbox	4-speed	4-speed	4-speed	4-speed	4-speed	4-speed	4-speed	4-speed
Differential lock	○	○	○	○	○	○	○	○
Powered rear wheels	○	○	○	○	○	○	○	○
Tyres								
Traction wheels	620/75 R34	620/75 R34	620/75 R34	620/75 R34	620/75 R34	620/75 R34	620/75 R34	620/75 R34
	650/75 R32	650/75 R32	650/75 R32	650/75 R32	650/75 R32	650/75 R32	650/75 R32	650/75 R32
	710/70R38	710/70R38	710/70R38	710/70R38	710/70R38	710/70R38	710/70R38	710/70R38
	800/65 R32	800/65 R32	800/65 R32	800/65 R32	800/65 R32	800/65 R32	800/65 R32	800/65 R32
	900/60 R32	900/60 R32	900/60 R32	900/60 R32	900/60 R32	900/60 R32	900/60 R32	900/60 R32
	1050/50 R32	1050/50 R32	1050/50 R32	1050/50 R32	1050/50 R32	1050/50 R32	1050/50 R32	1050/50 R32
Steering wheels	14.9 x 24	14.9 x 24	14.9 x 24	14.9 x 24	14.9 x 24	14.9 x 24	14.9 x 24	14.9 x 24
	460/70 R24	460/70 R24	460/70 R24	460/70 R24	460/70 R24	460/70 R24	460/70 R24	460/70 R24
	540/65 R24	540/65 R24	540/65 R24	540/65 R24	540/65 R24	540/65 R24	540/65 R24	540/65 R24
	480/70 R30	480/70 R30	480/70 R30	480/70 R30	480/70 R30	480/70 R30	480/70 R30	480/70 R30
	540/65 R30	540/65 R30	540/65 R30	540/65 R30	540/65 R30	540/65 R30	540/65 R30	540/65 R30
	600/65 R28	600/65 R28	600/65 R28	600/65 R28	600/65 R28	600/65 R28	600/65 R28	600/65 R28
	18.4 R30	18.4 R30	18.4 R30	18.4 R30	18.4 R30	18.4 R30	18.4 R30	18.4 R30
	620/75 R26	620/75 R26	620/75 R26	620/75 R26	620/75 R26	620/75 R26	620/75 R26	620/75 R26
	18.4 x 38	18.4 x 38	18.4 x 38	18.4 x 38	18.4 x 38	18.4 x 38	18.4 x 38	18.4 x 38
Dimensions								
With traction wheels	620/75 R34	650/75 R32	710/70 R38	800/65 R32	650/75 R32	710/70 R38	800/65 R32	900/60 R32
Maximum height in transport position (m)	3.93	3.92	3.96	3.92	3.92	3.96	3.92	3.96
Minimum overall width (m)	2.98	3.24	3.28	3.44	3.28	3.48	3.68	3.84
Maximum length without header with std. unloading auger (m)	9.07	9.07	9.07	9.07	9.07	9.07	9.07	9.07
Weight								
Standard version without header, without chopper (*)								
Self-levelling shoe (kg)	14,400	14,400	14,500	14,800	15,500	15,500	15,500	15,900
Fixed shoe (kg)	14,300	14,300	14,300	14,600	15,300	15,300	15,400	15,800
Cab								
Air-suspension seat	○	○	○	●	○	○	●	●
Passenger seat	○	○	○	●	○	●	●	●
Coolbox	○	○	○	●	○	●	●	●
Air-conditioning	●	●	●	●	●	●	●	●
Climate control	N/A	N/A	○	○	○	○	○	○
Heating	○	○	○	○	○	○	○	○
Remote controls for all functions	●	●	●	●	●	●	●	●
InfoView™ monitor with adjustable position	●	●	●	●	●	●	●	●
Automatic crop settings	●	●	●	●	●	●	●	●
Precision Farming	○	○	○	○	○	○	○	○

● Standard ○ Optional at extra cost – Not available (*) with 800/65 R32 traction tyres and 540/65 R24 Steering tyres - adjustable steering axle - full fuel tank