



		CR960	CR980
Grain header			
Cutting width			
High-Capacity grain header	(m)	5.18-9.15	5.18-9.15
Extra-Capacity grain header	(m)	6.10-9.15	6.10-9.15
Automatic header compensation and stubble height control		●	●
Lateral float		●	●
Autofloat		●	●
Knife speed	(cuts/min.)	1150	1150
Front face adjustment		●	●
Single location coupling		●	●
Feeding auger			
Full-width retractable fingers		●	●
Reel			
Diameter	(m)	1.07	1.07
Fully controlled reel		●	●
Maize headers			
Number of rows		8, flip-up	8, flip-up
Stalk choppers		○	○
Rotary dividers		○	○
Straw elevator			
Number of chains		3	3
Advanced stone detection		●	●
Feeder reverser		hydr.	hydr.
Longitudinal rotors			
Rotor diameter	(mm)	432	559
Rotor length	(mm)	2638	2638
Length of auger section	(mm)	390	390
Length of threshing section	(mm)	739	739
Length of separation section	(mm)	1090	1090
Length of discharge section	(mm)	419	419
Concaves			
Threshing concaves			
Wrap angle	(degrees)	86	84
Wrap angle with extension	(degrees)	121	123
Adjustment		Electric	Electric
Read out		Infoview monitor	Infoview monitor
Separation concaves			
Separation grates per rotor		3	3
Wrap angle	(degrees)	148	148
Beater			
Width	(mm)	1300	1560
Diameter	(mm)	400	400
Beater concave wrap angle	(degrees)	54	54
Total threshing and separation area	(m ²)	2.43	3.06
Cleaning			
Self-levelling cleaning shoe		●	●
Pre-cleaning system		●	●
Remote control sieve setting		○	○
Double-acting shaker shoe system		●	●
Total sieve area under wind control	(m ²)	5.4	6.5
Cleaning fan			
Number of blades		6	6
Variable speed range - optional - low	(rpm)	475 - 900	475 - 900
- standard - high	(rpm)	210 - 495	210 - 495
Double outlet fan with additional air-intake at the top		●	●
Electrical speed adjustment from the cab, with speed displayed on Infoview monitor		●	●

		CR960	CR980
Return system			
Roto-thresher™		Double	Double
Returns indicator on InfoView monitor		●	●
Grain elevator			
High capacity grain elevator with heavy duty chain & flaps		●	●
Graintank			
Capacity	(litres)	9000	10500
Central filling, folding bubble-up extension		●	●
Remote control graintank covers		●	●
Unloading auger			
Overtop unloading		●	●
Unloading speed	(litres/sec.)	105	105
Engine			
Type		Iveco Cursor	Iveco Cursor
Gross engine power ISO TR 14396, at rated speed	[kW/hp(CV)]	245 / 333	315 / 428
Governor type		Electronic	Electronic
Rated engine speed	(rpm)	2100	2100
Power boost	[kW/hp(CV)]	20 / 27	20 / 27
Fuel tank			
Capacity	(litres)	750	1000
Transmission			
Type		Hydrostatic	Hydrostatic
Gearbox		4-speed	4-speed
Differential lock		●	●
Powered rear wheels		○	○
Tyres			
Traction wheels		650/75 R32	650/75 R32
		710/70 R38	710/70 R38
		800/65 R32	800/65 R32
		900/60 R32	900/60 R32
		1050/50 R32	1050/50 R32
Steering wheels		460/70 R24	460/70 R24
		480/70 R30	480/70 R30
		540/65 R30	540/65 R30
		600/65 R28	600/65 R28
		18.4 x 38	18.4 x 38
Dimensions			
With traction wheels		710/70 R38	800/65 R32
Maximum height in transport position	(m)	3.96	3.92
Maximum width / offset in	(m)	3.25	3.7
Maximum length with extended unloading tube	(m)	9.97	9.97
Weight			
Standard version with header, without chopper	(kg)	15300	16500
Cab			
Air-suspension seat		●	●
Passenger seat		●	●
Coolbox		●	●
Air-conditioning		●	●
Automatic climate control		●	●
Heating		●	●
Remote controls for all functions		●	●
InfoView monitor with adjustable position		●	●
Automatic crop settings		●	●
Precision Farming		○	○

● Standard ○ Option – Not available